

Pi UV254Portable

UV254 Absorption and Transmission

With the UV254Portable range of UV254 hand held meters you get a simple and reliable means of testing any water for UVT and UVA. Essential for verifying an online analyzer reading or as an independent measurement.

- **Portable organics monitoring in water**
- **Measures UV254 (SAC or UVT)**
- **Accurate, stable, reliable, precise**
- **Fast response**
- **Easy to use**
- **Rugged**
- **Low cost**
- **Calibration memory (No DI water needed)**
- **Innovative technology**
- **Long lamp life**

Being able to get fast, reliable UV254 absorption, and therefore organics loading information is now a reality. Used to provide quick (<1min) information on site, the UV254Sense Portable provides an invaluable tool to water treatment engineers.

Applications

- **Enhanced coagulation jar testing**
- **Raw water surveys**
- **Treated water testing**
- **Online instrument verification**

Specification*

Range:	0-1.3 UVA, 5-100% UVT
Accuracy:	±0.5% FS
Resolution:	0.001 UVA, 0.1% UVT
Units:	cm ⁻¹
Path Length:	10mm
Calibration:	Calibration memory removes the need to re-zero to DI water
Self Diagnostics:	Notification of system failure
Operator Interface:	Easy to use, no complex configuration required
Display:	32 character backlit LCD
Wavelength:	253.7nm
Light Source:	Low pressure mercury UV lamp/UV LED



The Pi UV254Sense Portable for the measurement of UV254 Absorbance and UV254 Transmission can provide testing in both units of UV transmittance (UVT) and UV absorbance (UVA), and any of the meters can be equipped with our optional battery pack feature, allowing the meter to truly go anywhere, anytime. The patented Split-Sensor technology also allows for the unique ability to remember the meter's calibration, eliminating the need to calibrate (zero) the meter to a known pure (DI) water source before taking a measurement. This improves ease of use in the field for performing rapid grab sample testing of various water sources.

Lamp Life:	2 years
Dimensions:	22.1cm L (8.7") x 19.05cm W (7.5") x 9.9cm H (3.9")
Enclosure:	IP65 Rugged, compact, watertight and dustproof
Electrical:	12VDC 1A wall adapter (accepts 90-250VAC 50/60Hz), 12VDC car adapter
Storage Temp:	-20° to 60°C (-4° to 140°F)
Operating Temp:	0° to 45°C (32° to 113°F)
Weight:	1.81kg/4lbs
Warranty:	1 year
Technology:	Split-Sense
Options:	Battery power pack

**All subject to change without notice*