



FluoriSense

Continuous Online Fluoride Meter

The FluoriSense range of Fluoride Analysers from Pi utilise the very latest and best Fluoride sensors available in the world today for measuring the online Fluoride of any potable water. They are ion selective electrodes (ISEs) with solid polymeric junction, which use no reagents, are extremely stable, and have reduced maintenance and reduced whole life costs.

- **Up to 2 years continuous operation**
- **Stable and reliable - excellent process control**
- **Suitable for all potable waters**



The FluoriSense sensors and flow cells are available with different controllers giving you the same great performance with different communication, display, and control options. With the FluoriSense range of online Fluoride meters, you get everything that you need - and nothing that you don't.

"The Fluoride sensors from Pi are much more stable than others we've tried and give excellent results"

Chris Naidoo, NZ

CRONOS[®] FluoriSense



- High Quality - Lowest Cost
- Multilingual
- High resolution grayscale display
- 9 buttons for easy navigation
- Graphing and datalogging
- Enclosure; wall, panel, pipe or pole mounting. IP65/Nema 4x.
- Options:
 - **Modbus RS485/LAN**
 - **Profibus DPV 1**
 - **Up to 2 sensors**
 - **PID/flow proportional controls**
 - **Remote sensors**
 - **Colour display**

CRIUS[®] 4.0 FluoriSense



- High Quality - Lowest Cost
- Multilingual
- High resolution colour display
- Intuitive user interface
- Downloadable data logs
- Customisable home pages
- All CRONOS[®] options plus:
 - **Up to 4 sensors**
 - **Remote access via LAN**
 - **Remote access via 3G/4G**

For more information please see the individual brochures for CRONOS[®] and CRIUS[®] 4.0

Principle of Operation

Nearly all Fluoride Analysers are based on Fluoride ISEs. In some the accuracy is increased by continually dosing the sample with an Ionic Stabilising Solution, typically known as TISAB (Total Ionic Strength Adjustment Buffer). These buffers do help "fix" the ionic strength of a solution but in doing so introduce a cost and complexity that is considered by many to be unnecessary in drinking water fluoride dosing control.

The FluoriSense does not use TISAB and therefore is only suitable for use in applications where pinpoint accuracy is not critical and where the ionic strength of the water is relatively stable.

In many applications the FluoriSense is used primarily to ensure that the flow proportional dosing is working well and in these applications the FluoriSense is ideal providing a relatively low cost, easy to install and monitor, reliable solution. Pairing the FluoriSense sensor with the CRONOS®/CRIUS®4.0 controller means this kind of flow proportional dosing can be done without the need of PLCs or programming as it can all be controlled through the CRONOS®/CRIUS®4.0 out of the box. Adding the SMART pump integration from the CRIUS®4.0 controller means you can get a fully integrated dosing system for a fraction of the overall cost of existing systems.



Fluoride Sensor with cap

Specification*

Type:	ISE (Ion Specific Electrode)
Reference Type:	Solid polymer junction
Measurand:	Fluoride
Slope:	-56 ± 4mV at 25°C
Concentration Range:	1x10 ⁻⁶ M to saturation (0.02 ppm - saturation)
pH Range:	5 to 7 pH at 1 x 10 ⁻⁶ M
Temperature range:	0 to 80°C continuous
Electrode Resistance:	less than 50 MΩ
Reproducibility:	±2%
Minimum Sample Size:	300ml min ⁻¹
Size:	Electrode length - 155mm Body diameter - 12mm Cap Diameter - 16mm
Cable Length:	100cm
Calibration:	Manual using a test kit
Short Term Storage:	Rinse the electrode thoroughly with DI water and place the tip back in its cap.
Long Term Storage:	Rinse thoroughly with DI water and store dry. Replace the cap to protect the sensing element.

Even with the additional functionality that this unit has to offer, the purchase costs are typically very significantly less than its competitors.

Multi-Sensor Systems

The whole range of FluoriSense analysers can be fitted with additional sensors such as chlorine, ORP or pH. Please ask your local distributor for more details.

"Multi-sensor systems can save considerable sums without compromising measurement integrity"

Dr Craig Stracey, UK

Installation

The FluoriSense can be installed in a variety of auxiliary flow cells.



FluoriSense in a single closed flow cell



FluoriSense in a single open flow cell

****All subject to change without notice***